

## BELT OIL SKIMMER TOTE-IT

The skimmers of the Tote-It series are for stationary and portable use. The stabilizer bar of the standard version is 1,5 meter long. It can be also ordered in a length of up to 3 meters on request. There are two belt widths. The drive unit is available in coated steel and in stainless steel.

Type	Belt width	Belt Length	Material	Capacity
ST2CEL (TI02-060)	50 mm (2")	1520 mm (60")	Coated steel	~ 22 l/h
ST2SEL (TI02SS-060)	50 mm (2")	1520 mm (60")	Stainless steel	~ 22 l/h
ST2CEL (TI02-120)	50 mm (2")	3048 mm (120")	Coated steel	~ 22 l/h
ST2SEL (TI02SS-120)	50 mm (2")	3048 mm (120")	Stainless steel	~ 22 l/h
ST4CEL (TI04-060)	100 mm (4")	1520 mm (60")	Coated steel	~ 45 l/h
ST4SEL (TI04SS-060)	100 mm (4")	1520 mm (60")	Stainless steel	~ 45 l/h
ST4CEL (TI04-120)	100 mm (4")	3048 mm (120")	Coated steel	~ 45 l/h
ST4SEL (TI04SS-120)	100 mm (4")	3048 mm (120")	Stainless steel	~ 45 l/h

Type codes in brackets are older type codes. The performance data listed are non-binding guidelines for standard oil SAE 30.

Customized belt lengths from 1520 mm to 3048 mm available on request.

### Technical Data

Drive	Gearmotor 12 rpm
Voltage	1~ 230 V, 50 Hz (optional 115 V, 60 Hz)
Current consumption	1,3 A
Material	Base unit for types ST2CEL and ST4CEL of coated steel. Base unit for types ST2SEL and ST4SEL of stainless steel. Viper blades of Nitrile, optional of Viton or hybrid-ceramic.
Weight	~ 15,4 kg for belt width 50 mm (2") ~ 16,3 kg for belt width 100 mm (4")



Belt Oil Skimmer ST2CEL