

## TUBE OIL SKIMMER TUBETASTIC

The tube oil skimmer TubeTastic can be used on machining centers with little or no access to the coolant sump from above. This unit can be easily mounted on the side of virtually any machining center coolant sump. By use of an existing opening or making a small access cutout, the collector tube runs through the surface of the coolant and collects the unwanted oils. The oil then flows out of the discharge tube into any waste oil container for easy disposal.

Type	Schlauchlänge	Leistung
STUBE01F-12 (TU-12)	305 mm (12")	~ 5,5 l/h
STUBE01F-18 (TU-18)	452 mm (18")	~ 5,5 l/h
STUBE01F-24 (TU-24)	610 mm (24")	~ 5,5 l/h
STUBE01F-30 (TU-30)	762 mm (30")	~ 5,5 l/h

Type codes in brackets are older type codes. The performance data listed are non-binding guidelines based on standard oil SAE 30.

### Technical Data

Drive	Gearmotor 30 rpm, fan cooled
Voltage	1~ 230 V, 50 Hz (optional 115 V, 60 Hz)
Current consumption	1,5 – 2 A
Power cord	3-pole, 1 m
Material	Base unit of coated steel. Wiper of nitrile.
Operating temperature	max. 60 °C
Weight	approx. 3 kg



Tube Oil Skimmer STUBE01F

